



24 Hour Quick Ship Program



INDOOR

OUTDOOR

AmeriKooler is now offering a convenient, **24 Hour Quick Ship Program** to accommodate customers' demand for fast delivery of popular cooler and freezer sizes with Indoor and Outdoor Top Mount Self-Contained and Remote Refrigeration Systems.

INDOOR AND OUTDOOR COOLERS AND FREEZERS IN STOCK

6x6, 6x8, 6x10, 6x12
8x8, 8x10, 8x12

With Floor 7'-7" Height (coolers and freezers)
No Floor 7'-2 1/4" Height (coolers)

Your Choice of 30" or 36" Clear Door Opening, Centered

Top Mount Self-contained Units, Indoor and Outdoor 35°F, -10°F
Remote Systems, Outdoor 35°F, 0°F, -10°F
All Refrigeration with Mounted Components, 208-230/1/60

WARRANTIES

- DOW 50 year thermal warranty on AK-XPS4 insulation
- 15 year original panel warranty
- 1 year limited panel labor warranty
- 1 year original parts warranty
- Refrigeration system components will be covered per original equipment manufacturer's warranty terms and conditions

SPECIFICATIONS

- 4" thick AK-XPS4 insulation with R-values of R-29 for coolers and R-32 for freezers
- 26 gauge Acrylume® coated corrosion resistant stucco embossed Galvalume on all interior and exterior surfaces
- 30"W x 76"H or 36"W x 76"H flush mounted door
- 2 super cam-rise spring assisted hinges
- Deadbolt keyed handle latch
- Interior safety lock release handle
- Spring actuated door closer
- Digital LED thermometer with on and off pilot light switch
- Vapor proof light fixture centered on interior door jamb
- Smooth aluminum floor finish rated at 600 Lbs. per sq. ft. of uniformly distributed load
- Freezer door with temperature regulating thermostat and mounted and pre-wired PRV
- Floorless walk-ins with NSF vinyl screed
- Outdoor walk-in accessories include: rain roof membrane, exterior floor angles and door hood



National Sanitation Foundation



Underwriters Laboratories



City of Houston, TX
Public Works
and Engineering



State of Oregon
Building Codes
Division



New York City



EISA Energy Act Compliant
R-29 for Coolers
R-32 for Freezers

