

SCFM203



32.63" x 76" x 28.25" (H x W x D)

Commercially listed 19.8 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

19.8 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

Product Features:

| | |
|---|--|
| Large capacity | 19.8 cu.ft. of interior storage |
| Commercially approved | ETL-S listed to ANSI-NSF Standard 7 for commercial use |
| Factory installed lock | Keyed lock for a secure interior (2 keys included) |
| Manual defrost operation | Static cooling system with a rear-mounted drain for easier defrosting as needed |
| Counterbalanced hinges | The lid will remain open once lifted for safer loading |
| Thick insulation | 3 1/2" thick walls ensure proper insulation for reliable storage |
| Stainless steel front corner protectors | External "bumpers" included for easy installation to help protect the corners in high traffic environments |
| Hammered aluminum interior | Solid construction for durable storage in busy settings |
| Easy-grip handle | External handle for easy opening |



SCFM203 Specifications:

Overview

| | |
|----------------------------|---------------------|
| Height of Cabinet | 32.63" (83 cm) |
| Width | 76.0" (193 cm) |
| Depth | 28.25" (72 cm) |
| Depth with Handle | 30.0" (76 cm) |
| Capacity | 19.8 cu.ft. (561 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 3.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 210.0 lbs. (95 kg) |
| Shipping Weight | 220.0 lbs. (100 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101080802 |
| Freezer | |
| Door Swing | Lift-Up |
| Interior Height | 24.25" (62 cm) |
| Interior Width | 70.25" (178 cm) |
| Interior Depth | 20.75" (53 cm) |
| Thermostat Type | Dial |
| Refrigerant Type | R290a |
| Refrigerant Amount | 3.03 oz. |
| High Side PSI | 400.0 |
| Low Side PSI | 200.0 |
| Wheels | 6 |
| Compressor Step Height | 10.25" (26 cm) |
| Compressor Step Width | 11.75" (30 cm) |
| Compressor Step Depth | 20.75" (53 cm) |
| Temperature Range | -10 to -26°C |

