

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

Coldline C-1FF-TM 29" Solid Door Commercial Top Mount Reach-In Freezer



FEATURES

- Stainless steel interior and exterior
- Top-mounted compressor
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Locks and keys included
- Adjustable heavy-duty PVC coated shelves
- U-shaped door handle
- Electronic control system
- Perforated rear plenum
- Preinstalled heavy-duty casters with brakes
- Removable installation board
- Interior LED lighting
- Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	29"W x 32.2"D x 80.7"H
Interior Dimensions	24.4"W x 27.1"D x 56.7"H
Packaging Dimensions	30.3"W x 34"D x 84.5"H
Net Volume	21.68 cu. ft.
Unit Weight	267 lb.
Shipping Weight	300 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.2
Plug Type	NEMA 5-15P
Wattage	450 Watts

COOLING

Temperature Range	-7°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	3/8

CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	3 Qty: 20.9"W x 20.2"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	120 lb.
Adjustable Shelf	Yes
Interior Light	Yes
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: **C-1FF-TM**

MFR ITEM #:



NEMA 5-15P

