

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

Coldline CBT-36 36" Stainless Steel Refrigerated Salad Bar, Buffet Table



FEATURES

- 36" refrigerated buffet table
- Stainless steel exterior and interior
- Keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Adjustable heavy-duty PVC coated shelves
- Optional pan cover
- Auto defrost
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Fits 4" and 6" deep standard 1/3, 1/6 size food pans
- Hydro-Carbon R290 refrigerant

This Coldline stainless steel refrigerated salad bar, buffet table is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	36 7/16"W x 29 1/2"D x 35"H
Interior Dimensions	31 1/4"W x 19 7/8"D x 25 3/4"H
Packaging Dimensions	39"W x 33"D x 44"H
Net Volume	10.8 cu. ft.
Unit Weight	221 lb.
Shipping Weight	296 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4
Watts	384
Plug Type	NEMA 5-15P

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	3/7

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 15 13/16"W x 17 1/8"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Pan Capacity	(6) x 1/3 or (12) x 1/6
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: CBT-36

MFR ITEM #:



NEMA 5-15P

