

Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

SR-R24-LP 24" Liquid Propane Commercial Range with 4 Burners, 1 Oven



FEATURES

- 30,000 BTU per top burner
- 12" x 12" cast iron grates with aeration bowl
- Standing pilot light for individual burners
- 33,000 BTU static oven
- Oven interior side guides&bottom porcelain coated
- Oven thermostat adjusts from 200°F 500°F
- Manual gas controls
- Stainless steel front, back riser, and lift off shelf
- Casters standard, optional legs
- "Cool-to-the-touch" front s/s deck
- Flue located on back of unit for ample ventilation
- Easy to remove full width crumb tray
- Natural gas conversion Kit included
 - CSA
 - cCSAus
 - CSA Sanitation



U SR Brands Group is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



USR Brands, Inc. Phone: 800-764-1172 | www.usrbrands.com | sales@usrbrands.com



Datasheet

Project:

Model #:

Quantity:

Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	24"L x 32"D x 59"H	
Packaging Dimensions	28"L x 37"D x 44"H	
Unit Weight	268 lb.	
Shipping Weight	354 lb.	

COOKING

Numbers of Burners	4	
Burner BTU	30,000	
Numbers of Ovens	1	
Numbers of Oven Racks	1	
Oven BTU	33,000	
Oven Style	Standard Oven	
Max. Oven Temperature	500°F	
Total BTU	153,000	
Control Type	Maunal	
Gas Inlet Size	3/4″	
Power Type	Liquid Propane	

CONSTRUCTION

Exterior Material	Stainless Steel	
Frame Structure	Welded	
Number of Caster	(4) Qty: 2 with brakes, 2 without	
Pull Out Tray	"Yes"	

TECHNICAL DRAWING

MODEL: MFR MODEL:	SR-R24-LP Front Vi			
	L24*3			
		33.8.CT		
	0VEN INTO 			
	Side V			
	750mm [29,57]			
	(10,0*)			
	305mm [12*]	305mm84mm [12*] [3,3*]		
	1524mm (60,0*)			
		350mm		
	767mm [30,2*] 570mm Gos [22,4*]	(13,8*) (16,8*) (37,4*)		
		320mm 107mm [12,6*] [4,2*]		
	ADJUSTABLE FOO 152-190m 16-7, 2"1 470nm (18,5")			
Top View				
38mm [1,5"]Gas inlet				
		305mm		
		305mm (12.0*)		

