

# SBC635M7CMTWIN



49" x 23.63" x 25.5" (H x W x D)

Commercially listed dual tap coffee dispenser in black, with a combination nitro/flat coffee tap kit in stainless steel

## Highlights:

Commercially listed to NSF-7 standards

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Digital thermostat lets you set the perfect temperature for any cold brew

## Product Features:

|  |   |
|--|---|
| Commercially approved                        | ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments, with an NSF-listed tap kit  |
| Dispenses both flat and nitro-infused coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs                            |
| Complete tap kit                             | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs |
| Automatic defrost                            | Reduced user maintenance with auto defrost operation  |
| Digital thermostat                           | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit   |
| Ideal temperature                            | Operates between 33° and 50°F to keep your coffee stored at just the right serving temperature  |
| Fully finished black cabinet                 | Allows the dispenser to be used freestanding  |
| Reversible door                              | User-reversible door swing for added flexibility  |
| Casters included (ships unassembled)         | To make the unit portable, install this set of 2 1/2" high locking casters  |

## SBC635M7CMTWIN Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 49.0" (124 cm)     |
| Width                      | 23.63" (60 cm)     |
| Width with Door Open       | 25.0" (64 cm)      |
| Depth                      | 25.5" (65 cm)      |
| Depth with door at 90°     | 47.0" (119 cm)     |
| Capacity                   | 5.6 cu.ft. (159 L) |
| Defrost Type               | Automatic          |
| Door                       | Black              |
| Cabinet                    | Black              |
| US Electrical Safety       | UL                 |
| Canadian Electrical Safety | ULC                |
| Sanitation                 | ETL-S              |
| Energy Usage/Year          | 310.0kWh/year      |
| Amps                       | 0.86               |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 80.0 lbs. (36 kg)  |
| Shipping Weight            | 100.0 lbs. (45 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| Beer Dispenser             |                    |
| Door Swing                 | RHD                |
| Reversible                 | Yes                |
| Tap Kit                    | Yes                |
| Number of Taps             | 2                  |
| Thermostat Type            | Digital            |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 1.13 oz.           |
| High Side PSI              | 250.0              |
| Low Side PSI               | 110.0              |
| Inter Height               | 28.0" (71 cm)      |
| Interior Width             | 20.5" (52 cm)      |
| Interior Depth             | 19.0" (48 cm)      |
| Compressor Step Height     | 8.25" (21 cm)      |
| Wheel Qty                  | 4                  |
| Temperature Range          | 33° to 50° F       |

