

SBC635MBI7NKSSHV



33.5" x 24" x 25.88" (H x W x D)

Built-in commercially listed beer dispenser, auto defrost with digital thermostat, stainless steel door, thin handle, and black cabinet; no tapping equipment included

Highlights:

Commercially listed to NSF-7 standards

Full-sized capacity to hold half, quarter, 1/6 or mini kegs

Designed for built-in installation under the counter

Product Features:

| | |
|------------------------------|---|
| Commercially approved | ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments |
| Full-sized beer dispenser | Large 5.6 cu.ft. interior can accept a full half barrel keg, two 1/6 barrel kegs, or a pony keg |
| Built-in capable | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require extra space due to the door design. Width should be 25" to 25 1/4". For more information, see the user manual |
| Stainless steel wrapped door | Durable design with lasting elegance |
| Professional handle | Thin (14mm diameter) stainless steel handle mounted vertically for a sleek look that matches many popular styles of cabinetry |
| Automatic defrost | Reduced user maintenance with auto defrost operation |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |
| Ideal beer temperature | Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature |
| Fully finished black cabinet | Allows the unit to be used freestanding |



SBC635MBI7NKSSHV Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 33.5" (85 cm) |
| Width | 24.0" (61 cm) |
| Width with Door Open | 25.25" (64 cm) |
| Depth | 25.88" (66 cm) |
| Depth with door at 90° | 47.5" (121 cm) |
| Capacity | 5.6 cu.ft. (159 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 0.86 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Shipping Weight | 140.0 lbs. (64 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Beer Dispenser | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Thermostat Type | Digital |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.13 oz. |
| High Side PSI | 250.0 |
| Low Side PSI | 110.0 |
| Inter Height | 28.0" (71 cm) |
| Interior Width | 20.5" (52 cm) |
| Interior Depth | 19.0" (48 cm) |
| Compressor Step Height | 8.25" (21 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 33° to 50° F |

