

Datasheet

Gldline

Project:

Model #:

Approval:

Quantity:

For Commercial Use Only

UC-60R-BS 60" Work Top Refrigerator with Backsplash

FEATURES

- Holds temperature between 33°F to 41°F
- · Stainless steel interior, exterior, and backsplash
- Aluminum back
- Self-closing doors with 90 degree stay open feature
- Adjustable PVC shelves
- Electronic control system
- Preinstalled 5" heavy-duty casters with brakes
- Removable insallation board
- Hydro-Carbon R290 refrigerant
- Low profile casters lower height by 1.5" (optional)

The Coldline UC 60" is a great refrigerator for an undercounter or worktop application. This 2 door unit provides 15 cu. ft. of storage and a thick 60" stainless steel work surface. Interior and exterior made of stainless steel. Wheels, adjustable shelves, and self-closing doors come standard on all units. Eco-friendly R290 refrigeration system maintains 33 to 41 degree temperature to keep your food in the safe zone.

- cETLus Listed
- ETL Sanitation Listed Conforms to UL & NSF Standards



Use SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.





Project:

Model #:

For Commercial Use Only

Quantity:

Approval:

TECHNICAL DATA

DIMENSIONS

60.2″W x 29.5″D x 39.5″H
60.2″W x 29.5″D x 38″H
55.6″W x 22.9″D x 23.5″H
63"W x 32.3"D x 38.5"H
35.3″
15 cu. ft.
269lb.
339lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.9
Plug Type	NEMA 5-15P
Power Cord Length	84″

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/5

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 20.8″W x 17″D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.

TECHNICAL DRAWING



